

Bath Fan/Light

MODEL #696



- 100 CFM 4.5 Sones.
- Designer styled white polymeric grille complements virtually any decor.
- Bright 100-watt light capacity. Bulb not included
- Housing lined with 1/2" acoustic insulation.
- 15 amp circuit acceptable.
- Type IC (Insulation Contact).
- Does not include heater.

Quiet combination units, built with high performance blowers, acoustic insulation, and attractive styling.

FEATURES

GRILLE:

- White polymeric grille
- Directional vanes for heat and exhaust
- Snap-in light diffusing lens for 100W light

VENTILATOR:

- Resilient anti-vibration mounts
- Plug-in, permanently lubricated motor
- Low sound, high performance blower wheel

HEATER (HFL695 Only):

- 1300 watts, with metal blower wheel for efficient, even heating
- Plug-in, permanently lubricated motor - functions independent of ventilator

HOUSING:

- 1/2" acoustic insulation
- Adjustable mounting brackets up to 24"
- Polymeric damper/duct connector with 2" long tapered sleeve and no metallic clatter
- Compact 23 gage steel housing finished with electrically-bonded epoxy paint

NOTE: For installation in ceilings up to 12/12 pitch

- Suitable for use in insulated ceilings (Type I.C.)
- Use supply wiring rated for at least 90°C.

CONTROLS: Designed by Broan for use with this product (purchase separately)

- Model 57V (Ivory) / 57W (White) Electronic Variable Speed Control
- Model 59V (Ivory) / 59W (White) 60-Minute Time Control
- Model 61V (Ivory) / 61W (White) 15-Minute Time Control
- Model 62V (Ivory) / 62W (White) 15-Minute Time Control with Two-Rocker Switch

- Model 63V (Ivory) / 63W (White) 60-Minute Time Control with Single-Rocker Switch
- Model 64V Fan/Light Delay-Off Control
- Model 65V (Ivory) / 65W (White) Three Function Control (Brass Finish Metal Wall Plate)
- Model 66V (Ivory) / 66W (White) Three Function Control (Chrome Finish Metal Wall Plate)
- Model 67V (Ivory) / 67W (White) Three Function Control (Chrome Finish Metal Wall Plate)
- Model 68V (Ivory) / 68W (White) Two Function Control

TYPICAL SPECIFICATION

Combination unit shall be Broan Model HFL695 (Broan Model 696).

Unit shall have steel housing finished with electrically-bonded epoxy and insulated with at least 1/2" of acoustical insulation. Housing shall have adjustable mounting brackets.

Unit shall have directional vanes for heat and exhaust and must be rated to handle a 100W bulb.

Fan, heater and light shall be separately controllable. Motors shall be permanently lubricated and mounted with resilient anti-vibration mounts. RPM not to exceed number listed for each model.

Air delivery shall be no less and sound levels no greater than listed for each model. All air and sound ratings shall be certified by AMCA and/or HVI. Unit to be U.L. listed. Model HFL695 and 696 suitable for use in insulated ceilings. (Type I.C.).



"Broan-NuTone LLC certifies that the models shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 (and AMCA Publication 311 if sound is also certified) and comply with the requirements of the AMCA Certified Ratings Program."

